

# Socket communication

The client sends requests to the server over a TCP socket connection, and the server responds to these requests. Here are the basic steps involved in integrating software systems or components using TCP socket communication:

1. **Select a protocol:** TCP/IP is a common protocol for socket communication, but other protocols like UDP can also be used depending on the requirements.
2. **Determine the message format:** Decide on the format of the messages that will be exchanged between the client and server. This could be a simple text-based format or a more complex binary format.
3. **Define the communication interface:** Define the functions or APIs that will be used for communication between the client and server.
4. **Create the server:** Write the code for the server that listens for incoming client connections and handles incoming requests.
5. **Create the client:** Write the code for the client that connects to the server and sends requests.
6. **Handle errors:** Implement error handling mechanisms to ensure that communication errors are handled gracefully and do not cause the system to crash or become unstable.
7. **Test and iterate:** Test the system thoroughly and make any necessary changes or improvements to ensure that it is functioning correctly.

## Features:

- Socket ::= IP address + (TCP/UDP) port number. A Socket is a combination of ip address and port number.
- TCP Sockets provides 'real-time' data transfer
  - binary data transfer but can be normal text or JSON, XML as well
  - no direct method sharing (can be implemented by hand)
  - TCP and UDP connections are possible. UDP is min 3 times quicker but one-way communication
- Persistent or On-Demand communication channel
  - because of connection time-loss usually persistent channels are better, but periodically 'ping' messages should be sent. (in order to avoid connection closing). In case of any problems reconnection is possible
  - in case of UDP channels an extra TCP channel is available for synchronizing - in online games
- Results in the fastest possible transmission:
  - Where the number of transactions per second up to ~ 50 transactions, there should have been applied. (20ms / sec transfer)

## [Java example for Blocking and Non-Blocking Socket](#)

From:  
<https://edu.iit.uni-miskolc.hu/> - Institute of Information Science - University of Miskolc

Permanent link:  
[https://edu.iit.uni-miskolc.hu/tanszek:oktatas:integration\\_based\\_on\\_tcp\\_ip\\_sockets?rev=1678032691](https://edu.iit.uni-miskolc.hu/tanszek:oktatas:integration_based_on_tcp_ip_sockets?rev=1678032691)

Last update: 2023/03/05 16:11

