

Quality measurement system example

We send states to a message queue named 'qualityQueue', which stores simple status messages of a quality assurance system. Create a multi-component application that communicates with the message queue through two clients in the following way:

1. The first client connects to the sensor placed on the measuring machine and randomly sends GOOD, EXCELLENT, and WRONG messages to the 'qualityQueue' message queue every second.
2. Create a component that reads and collects the 'GOOD', 'EXCELLENT', and 'WRONG' messages from the qualityQueue queue. After receiving 10 identical messages, it sends a message to the 'qualityStatistics' queue indicating that it has processed 10 messages of a certain quality.
3. Create a second client that reads the statistics from the 'qualityStatistics' queue and prints to the console, for example, '10 'WRONG' messages has been processed'.

```
flowchart TB
    subgraph MQ [MQ]
        direction TB
        qualityQueue[qualityQueue]
        qualityStatistics[qualityStatistics]
    end
    subgraph Clients
        direction TB
        Client1[Client 1 (Sensor Data Sender)]
        Client2[Client 2 (Quality Message Consumer)]
        Client3[Client 3 (Statistics Consumer)]
    end
    Client1 -->|sends GOOD/EXCELLENT/WRONG| MQ
    MQ -->|collects messages| Client2
    Client2 -->|sends batch of 10 messages| MQ
    MQ -->|receives and prints batches| Client3
    subgraph DockerMachine [Docker Machine]
        MQ
        Clients
    end
    classDef machine fill:#f9f,stroke:#333,stroke-width:2px;
    classDef clients fill:#ccf,stroke:#333,stroke-width:2px;
    class DockerMachine machine;
    class Clients clients;
```

Let's try to solve the task with <http://docker.iit.uni-miskolc.hu> framework.

Starting RabbitMQ in Docker

To solve the task, it is recommended to start multiple instances (terminals). The first terminal will start the RabbitMQ server. Open a new terminal (node 1) and run the following command:

```
docker run -it --rm --name rabbitmq -p 5672:5672 -p 15672:15672
rabbitmq:management-alpine
```

After running the command above, the RabbitMQ management console will be accessible on port 15672, using the credentials guest/guest. In the left-side menu, you can find the internal IP address (10.x.y.z) of node1, which can be used in the clients and processors.

Create another terminal and execute the following command:

```
pip install pika
```

This command installs the pika module, which provides the connection to RabbitMQ.

Create the *quality_message_sender.py*:

Use the appropriate IP address in the *init(self)* method.

```
import pika
import random
import time
```

```
class QualitySender:
    def __init__(self):
        self.connection =
pika.BlockingConnection(pika.ConnectionParameters('10.x.y.z'))
        self.channel = self.connection.channel()
        self.channel.queue_declare(queue='qualityQueue')

    def start_sending(self):
        qualities = ['GOOD', 'EXCELLENT', 'WRONG']
        while True:
            quality = random.choice(qualities)
            self.channel.basic_publish(exchange='',
routing_key='qualityQueue', body=quality)
            print(f'Sent quality: {quality}')
            time.sleep(1)

    def close_connection(self):
        self.connection.close()

if __name__ == '__main__':
    sender = QualitySender()
    try:
        sender.start_sending()
    except KeyboardInterrupt:
        sender.close_connection()
```

Let's create the *quality_message_consumer.py* file, and the create statistics:

(do not forget to create it in an other terminal, and run *pip install pika* and set the proper IP in *pika.ConnectionParameters()*)

```
import pika

class QualityConsumer:
    def __init__(self):
        self.connection =
pika.BlockingConnection(pika.ConnectionParameters('10.x.y.z'))
        self.channel = self.connection.channel()
        self.channel.queue_declare(queue='qualityQueue')
        self.channel.queue_declare(queue='qualityStatistics')
        self.message_count = {'GOOD': 0, 'EXCELLENT': 0, 'WRONG': 0}

    def start_consuming(self):
        def callback(ch, method, properties, body):
            quality = body.decode()
            self.message_count[quality] += 1
            print(f'Received quality: {quality}')
            if self.is_batch_completed():
                self.send_statistics()
```

```

        self.reset_message_count()

        self.channel.basic_consume(queue='qualityQueue',
on_message_callback=callback, auto_ack=True)
        self.channel.start_consuming()

    def send_statistics(self):
        for quality, count in self.message_count.items():
            if count > 0:
                message = f'{count} {quality} messages has been processed'
                self.channel.basic_publish(exchange='',
routing_key='qualityStatistics', body=message)
                print(f'Sent statistics: {message}')

    def reset_message_count(self):
        for quality in self.message_count:
            self.message_count[quality] = 0

    def is_batch_completed(self):
        return sum(self.message_count.values()) >= 10

    def close_connection(self):
        self.connection.close()

if __name__ == '__main__':
    consumer = QualityConsumer()
    try:
        consumer.start_consuming()
    except KeyboardInterrupt:
        consumer.close_connection()

```

The third components prints the statistics. Let's create an other instance (terminal) and create statistics_consumer.py

```

import pika

# RabbitMQ settings
connection = pika.BlockingConnection(pika.ConnectionParameters('10.x.y.z'))
channel = connection.channel()

channel.queue_declare(queue='qualityStatistics')

def callback(ch, method, properties, body):
    message = body.decode()
    print(f'{message}')
    ch.basic_ack(delivery_tag=method.delivery_tag)

channel.basic_consume(queue='qualityStatistics',
on_message_callback=callback)

print('Waiting for quality statistics...')

```

`channel.start_consuming()`

From:

<https://edu.iit.uni-miskolc.hu/> - **Institute of Information Science - University of Miskolc**

Permanent link:

https://edu.iit.uni-miskolc.hu/tanszek:oktatas:iss_t:rabbitmq?rev=1713247684

Last update: **2024/04/16 06:08**

