

What does software integration mean?

Definition

Software integration is a development process in which separate software systems—applications and components—are connected so they work together to form a new, unified system.

Phases

1.) Requirements assessment and planning

- requirements assessment: identifying user needs and business requirements
- planning: developing the integration strategy, designing the system architecture and integration points

2.) Requirements analysis and specification

- analysis: detailed assessment of required functions and the capabilities of existing systems
- specification: definition of interfaces and data exchange formats

3.) Development and implementation

- development: creation of integration code for existing systems
- implementation: deployment of new components and modification of existing ones

4.) Testing and validation

5.) Maintenance and support

Legacy Systems

Definition The term legacy system refers to IT systems that use older (possibly obsolete) technologies but are still actively operating and play an essential role in an organisation's everyday operation.

Why use legacy systems?

- Long lifetime and stability: Many legacy systems have operated reliably for years or even decades. If a system functions well and is mission-critical, there is often no compelling reason to replace it.
- Cost considerations: Replacing an entire system can be extremely expensive.
- Complexity: Legacy systems are often deeply integrated into other organizational processes and systems.
- Risk avoidance: Organizations often avoid the risk of replacement

Why Are They Not Replaced?

- Cost and lack of resources: Replacement is often not economically feasible, and risk estimation

can be difficult due to strict security requirements.

- Disruption of business processes: Introducing a new system may significantly disrupt daily operations. Many organizations prioritize operational stability (e.g., banking institutions).

Solutions

- Gradual migration: Instead of replacing the entire system at once, organizations incrementally migrate to new systems by replacing specific components or functionalities.
- Outsourcing maintenance and operation: Maintenance and operation of legacy systems may be delegated to external service providers, reducing internal costs and specialized staffing requirements.

Overview of Integration Strategies

Point to Point connection

Components connect directly to each other, typically via file transfer or direct database access. There is no intermediary layer, therefore communication is fast. Initially, it is easy to implement.

flowchart LR
%% Nodes
R[Radiology] EMR[EMR] CDB[Central Database] PS[Patient Search]
PDB[Patient DB] ER[Emergency Dept.] FIN[Billing / Finance] PHARM[Pharmacy]
%% Layout helpers (optional)
%% Try to mimic the original positions by grouping subgraph
Left[] direction TB
R PS FIN
end
Middle[] direction TB
EMR PDB PHARM
end
Right[] direction TB
CDB ER
end
%% Connections (based on the diagram)
R <--> PS
PS <--> EMR
PS --> PDB
PS --> FIN
EMR --> PDB
EMR --> FIN
EMR <--> CDB
PDB <--> ER
PDB <--> PHARM
ER --> PHARM
PHARM --> ER
CDB --> ER
ER --> CDB

Disadvantages - Challenges

- Difficult to scale
- Future expansion can become complex
- The number of connections grows exponentially $\rightarrow n(n-1)/2$ connections
- Fragile architecture, as monitoring and troubleshooting errors are difficult

Middleware Integration

Components do not connect to each other directly; instead, they communicate through a central intermediary (e.g., API Gateway, Application Server, Enterprise Service Bus – ESB).

The intermediary layer handles different communication protocols.

- Monitoring capabilities: communication tracking and centralized supervision
- Improved scalability

- Centralized functions: authorization management and transaction handling

Disadvantages - Challenges

- Complexity: system development costs are high
- Monolithic architecture – one central server serving many clients

flowchart TB
 EMR[EMR] --> MW[Message Oriented Middleware]
 RAD[Radiology] --> MW
 FIN[Billing and Finance] --> MW
 ER[Emergency Department] --> MW
 MW --> PS[Patient Search]
 MW --> PDB[Patient Database]
 MW --> CDB[Central Database]
 MW --> PHARM[Pharmacy]

Message Queue-Based Integration

Components do not connect to each other directly; instead, they communicate via message queues.

Messages are processed asynchronously.

- Monitoring capabilities: use of specialized queues (e.g., Dead Letter Queue – DLQ)
- Highly scalable architecture
- Naturally suited for cloud-based systems

Disadvantages - Challenges

- Complexity: system development costs are high
- Requires advanced expertise and careful architectural design

flowchart TB
 subgraph Top_layer [Top layer systems]
 RAD[Radiology]
 EMR[EMR]
 FIN[Billing]
 ER[Emergency Department]
 end
 subgraph Bottom_layer [Bottom layer systems]
 PS[Patient Search]
 PDB[Patient Database]
 CDB[Central Database]
 PHARM[Pharmacy]
 end
 RAD --> Q1[Queue 1]
 EMR --> Q1
 FIN --> Q2[Queue 2]
 ER --> Q3[Queue 3]
 Q1 --> PS
 Q1 --> PDB
 Q2 --> CDB
 Q3 --> PHARM

Data Sharing

A simple approach to integration is data sharing.

Data sharing-based integration aims to transfer and share data between systems. This enables individual systems to access and utilize data stored in other systems.

Data sharing can take several forms:

Comparison of Data Sharing Approaches

- **Data Migration** is typically a one-time process: It is suitable for system replacement or major upgrades, but it does not ensure continuous consistency.
- **Data Synchronization** provides ongoing consistency between systems: It is appropriate when multiple systems must maintain aligned datasets over time.
- **Data Sharing Services** enable real-time access to shared data: They are ideal for modern distributed and cloud-based architectures that require immediate data availability.

File-Based Data Sharing

The most fundamental method of data sharing.

One application writes data, while another application reads data from the same file.

The data files are stored in a central location — such as a shared folder (e.g., NFS) or an (S)FTP server.

The information flow is unidirectional: $A \rightarrow B$.

Data Encoding

Most file-based integration approaches use text-based files.

The most common formats are:

- Plain text
- XML
- JSON (in modern systems)

Raw text formats may use:

- Fixed-length records
- Variable-length records (commonly used in billing and financial systems)

For variable-length records, a delimiter is required to separate data fields. The most widely known method is CSV (Comma-Separated Values).

flowchart LR
A[System A] -- writes --> STORAGE[Shared Folder\nFTP Server]
B[System B] -- reads --> STORAGE

File-Based Integration with Lock Mechanism

State Files

State files can be used to track the processing status of data files.

These files may contain the current processing state, such as:

- "in progress"
- "completed"
- "failed"

File-Based Integration with Lock Mechanism

State Files

State files can be used to track the processing status of data files.

These files may contain the current processing state, such as:

- "in progress"
- "completed"
- "failed"

flowchart LR A[System A] STORAGE[Shared Folder / FTP Server] LOCK[(data.lock)] B[System B] A -- "1) create lock" --> LOCK A -- "2) write data" --> STORAGE B -- "3) detect lock" --> LOCK B -- "waits" --> STORAGE A -- "4) remove lock" --> LOCK B -- "5) read data" --> STORAGE

Lock File Mechanism

1) Lock file creation: System A begins processing a data file and creates a lock file, for example: data.lock.

2) Writing phase: System A creates or writes the data file while *data.lock* exists. System B attempts to access the data file but detects that the lock file exists, therefore it waits.

3) Completion: System A finishes processing and removes the data.lock file.

4) Reading phase: System B detects the data.lock file has been removed and it can begin its own processing.

Purpose of the Lock Mechanism

This method ensures that only one system processes the data file at a time, preventing data conflicts and inconsistencies.

The use of lock files is a simple and effective technique for process synchronization and coordination in file-based integration.

Last
update: 2026/02/15 21:52 tanszek:oktatas:iss_t:software_integration https://edu.iit.uni-miskolc.hu/tanszek:oktatas:iss_t:software_integration?rev=1771192375

From:
<https://edu.iit.uni-miskolc.hu/> - **Institute of Information Science - University of Miskolc**

Permanent link:
https://edu.iit.uni-miskolc.hu/tanszek:oktatas:iss_t:software_integration?rev=1771192375

Last update: **2026/02/15 21:52**

