

Exercise

Create a simplified FTP (file transport) client and server where the client can send or download text files from the server:

General use-cases

1.) Client connects to the server and sends a 'file listing' message
2.) Server sends back the list of the downloadable files
3.) Client lists the files and asks the user what action they want to take? Upload or download? ('u' or 'd')
4.) In both cases the user must give the full file name with extension
5.) The client sends the selected file to the server (upload) or downloads the selected file from the server to a specific directory.

Server viewpoint

1.) After connecting, it reads the files from the /store subdirectory and sends the file names to the client after receiving the listing message.
2.) We are waiting for the client's 'u' or 'd' operation
3.) We get a filename from the client and if the action is 'd' (download), we read the file content and return its contents
4.) If the operation is 'u' (upload), we open a new file with the specified name and wait for the data to be written to the file.

Client viewpoint

1.) The client connects and waits for the list of files coming back and writes it to the console
2.) We ask for the "u" or "d" key
3.) Then we'll ask for the file-name as well.
4.) The client reads the files from the /files folder, or creates the downloaded file here
5.) If you press "d", it creates /files/ and writes data from the server
6.) If you press "u", /files/ is sent to the server

Starting point of implementation

1.) Traditional blocked TCP based socket server class in Java

Socket server source code

```
import java.io.IOException;
import java.io.ObjectInputStream;
```

```
import java.io.ObjectOutputStream;
import java.net.ServerSocket;
import java.net.Socket;

public class Server {
    ServerSocket providerSocket;
    Socket connection = null;
    ObjectOutputStream out;
    ObjectInputStream in;
    String message;

    Server() {
    }

    void run() {
        try {
            // 1. create a socket server listening to port 8080
            providerSocket = new ServerSocket(8080, 10);
            // 2. waiting for the connection (here we are waiting until
            next connection)
            connection = providerSocket.accept();
            // 3. create Input and Output streams
            out = new ObjectOutputStream(connection.getOutputStream());
            in = new ObjectInputStream(connection.getInputStream());
            // 4. socket communication
            do {
                try {
                    message = (String) in.readObject();
                    System.out.println("client>" + message);
                    if (message.equals("bye")) {
                        sendMessage("bye");
                    }
                } catch (ClassNotFoundException classnot) {
                    System.err.println("Data received in unknown
format");
                }
            } while (!message.equals("bye"));
        } catch (IOException ioException) {
            ioException.printStackTrace();
        } finally {
            // 4: close connection
            try {
                in.close();
                out.close();
                providerSocket.close();
            } catch (IOException ioException) {
                ioException.printStackTrace();
            }
        }
    }
}
```

```
void sendMessage(String msg) {
    try {
        out.writeObject(msg);
        out.flush();
        System.out.println("server>" + msg);
    } catch (IOException ioException) {
        ioException.printStackTrace();
    }
}

public static void main(String args[]) {
    Server server = new Server();
    while (true) {
        server.run();
    }
}
}
```

Socket client source

```
import java.io.IOException;
import java.io.ObjectInputStream;
import java.io.ObjectOutputStream;
import java.net.Socket;
import java.net.UnknownHostException;

public class Client {
    Socket requestSocket;
    ObjectOutputStream out;
    ObjectInputStream in;
    String message;

    Client() {
    }

    void run() {
        try {
            // 1. try to connect to the socket: localhost:8080
            requestSocket = new Socket("localhost", 8080);
            // 2. Input and Output streams
            out = new
ObjectOutputStream(requestSocket.getOutputStream());
            in = new ObjectInputStream(requestSocket.getInputStream());
            // 3: communications
            do {
                try {
                    sendMessage("Hello server");
                    sendMessage("bye");
                    message = (String) in.readObject();
                }
            }
        }
    }
}
```

```
        } catch (Exception e) {
            System.err.println("data received in unknown
format");
        }
    } while (!message.equals("bye"));
} catch (UnknownHostException unknownHost) {
    System.err.println("You are trying to connect to an unknown
host!");
} catch (IOException ioException) {
    ioException.printStackTrace();
} finally {
    // 4: close connection
    try {
        in.close();
        out.close();
        requestSocket.close();
    } catch (IOException ioException) {
        ioException.printStackTrace();
    }
}
}

void sendMessage(String msg) {
    try {
        out.writeObject(msg);
        out.flush();
        System.out.println("client>" + msg);
    } catch (IOException ioException) {
        ioException.printStackTrace();
    }
}

public static void main(String args[]) {
    Client client = new Client();
    client.run();
}
}
```

2.) Hagyományos UDP alapú kommunikáció

2.a) Az alábbi Ágens küld egy üzenetet és a 8080-as porton várja a választ rá, ugyancsak UDP-vel. Az eclipse fejlesztőkörnyezetben a consolon beírt szöveget ctrl+z leütésével lehet elküldeni.

Feladat: módosítsuk a kódot, hogy át tudjon küldeni egy beégetett nevű, és létező, 2 kbyte-nál nagyobb szöveges vagy kép állományt és ellenőrizzük a sikeres küldést.

```
package org.ait;

import java.io.BufferedReader;
```

```
import java.io.InputStreamReader;
import java.net.DatagramPacket;
import java.net.DatagramSocket;
import java.net.InetAddress;

public class UDPClient {
    public static void main(String args[]) throws Exception {
        BufferedReader inFromUser = new BufferedReader(new
InputStreamReader(System.in));
        DatagramSocket clientSocket = new DatagramSocket();
        InetAddress IPAddress = InetAddress.getByName("localhost");

        byte[] sendData = new byte[1024];
        byte[] receiveData = new byte[1024];

        String sentence = inFromUser.readLine();
        sendData = sentence.getBytes();

        DatagramPacket sendPacket = new DatagramPacket(sendData,
sendData.length, IPAddress, 8080);
        clientSocket.send(sendPacket);

        DatagramPacket receivePacket = new DatagramPacket(receiveData,
receiveData.length);
        clientSocket.receive(receivePacket);
        String modifiedSentence = new String(receivePacket.getData());

        System.out.println("átalakítva:" + modifiedSentence);
        clientSocket.close();
    }
}
```

2.b) Az UDP szerver a 8080-as porton várja az ágensek üzeneteit és nagybetűre konvertálva visszaküldi a kliens UDP socketre.

```
package org.ait;

import java.net.DatagramPacket;
import java.net.DatagramSocket;
import java.net.InetAddress;

public class UDPServer {
    public static void main(String args[]) throws Exception {

        DatagramSocket serverSocket = new DatagramSocket(8080);

        byte[] bytesReceived = new byte[1024];
        byte[] bytesSent = new byte[1024];

        DatagramPacket receivePacket = new DatagramPacket(bytesReceived,
```

```
bytesReceived.length);  
    // itt várakozik ameddig adat jön a 8080-as porton  
    serverSocket.receive(receivePacket);  
  
    String szoveg = new String(receivePacket.getData());  
  
    System.out.println("kaptam: " + szoveg);  
  
    InetAddress IPAddress = receivePacket.getAddress();  
    int port = receivePacket.getPort();  
  
    String nagybetűsSzöveg = szoveg.toUpperCase();  
    bytesSent = nagybetűsSzöveg.getBytes();  
  
    // visszaküldi  
    DatagramPacket sendPacket = new DatagramPacket(bytesSent,  
bytesSent.length, IPAddress, port);  
    serverSocket.send(sendPacket);  
    serverSocket.close();  
  
    }  
}
```

From:

<https://edu.iit.uni-miskolc.hu/> - Institute of Information Science - University of Miskolc

Permanent link:

https://edu.iit.uni-miskolc.hu/tanszek:oktatas:tcp_socket_connection?rev=1677426327

Last update: **2023/02/26 15:45**

