

How Can We Define Languages in Computer Science?

Several scientific methods have been developed to precisely define the syntactic rules of languages.

Backus-Naur Form (BNF):

A **meta-language** used to describe the syntax of languages.

<name>	meta-symbol
::=	definition
	alternative
{expression}	repetition (minimum and maximum repetitions can be specified using subscripts)
GOTO	terminal symbol (in quotes for clarity, can also use apostrophes instead)

1. Example: Syntax of License Plates

Let's start with a few typical examples and try to generalize:

ABC-1234, GHT-234, HSD-333, AI-BB-654

Syntax definition: $\$ \$ \langle \text{license_plate} \rangle ::= \langle \text{newType} \rangle \mid \langle \text{oldType} \rangle \ \ \ \langle \text{oldType} \rangle ::= \{ \langle \text{letter} \rangle \}_3^3 - \{ \langle \text{number} \rangle \}_3^3 \ \ \ \langle \text{newType} \rangle ::= \{ \langle \text{letter} \rangle \}_2^2 - \{ \langle \text{letter} \rangle \}_2^2 - \{ \langle \text{number} \rangle \}_3^3$
 $\ \ \ \langle \text{letter} \rangle ::= A|B|C\dots|Z \ \ \ \langle \text{number} \rangle ::= 0|1|2|3|4|5|6|7|8|9 \ \ \ \$ \$$

2. Example: Syntax of Phone Calls in Hungary

Let's list a few examples and try to generalize:

062012345, +36301234567, 0680460046

Syntax definition: $\$ \$ \langle \text{phone call} \rangle ::= \{ \langle \text{prefix} \rangle \}_0^1 \langle \text{city} \rangle \langle \text{customer} \rangle \ \ \ \langle \text{prefix} \rangle ::= \{ + \}_0^1 36|06 \ \ \ \langle \text{city} \rangle ::= \{ \langle \text{number} \rangle \}_1^2 \ \ \ \langle \text{customer} \rangle ::= \{ \langle \text{number} \rangle \}_6^7 \ \ \ \langle \text{number} \rangle ::= 0|1|2|3|4|5|6|7|8|9 \ \ \ \$ \$$

From:

<https://edu.iit.uni-miskolc.hu/> - Institute of Information Science - University of Miskolc

Permanent link:

https://edu.iit.uni-miskolc.hu/tanszek:oktatas:techcomm:bn_formulas?rev=1728318567

Last update: **2024/10/07 16:29**

