

Error Detection and Correction Using Hamming Codes

Hamming codes are a family of error-correcting codes that can detect up to two-bit errors and correct single-bit errors in transmitted data. They use the Hamming distance concept to determine where errors may have occurred.

If we have (m) number of data bits then let's attach (r) number of redundant parity bits to it, so the whole bit length will be:

$$n = m + r$$

If two code-words are given, for example : **0101110** and **001111110** and the only difference between them is 1 bit, then the 'Hamming distance' of these code-words will be 1. This is an interesting measure for distance because it does not matter which bit in the row is different or whether it belongs to a binary or decimal system. So for example : **45635263** and **45615263** have the Hamming distance of 1 too. It does not matter that 10 different digits could be in the place of the wrong digit.

The **Hamming-style** correction code supposed to increase the number of parity bits. To correct single bit errors we have to use k number of parity bits using this formula:

$$n + 1 \leq 2^k$$

According to this formula the necessary number of parity bits which are needed to correct single bit errors are stated in the following table (for different word lengths):

word length	number of parity bits	whole bit length	% of added bits
4	3	7	66
8	4	12	50
16	5	21	31
32	6	38	19
64	7	71	11
128	8	136	6
256	9	265	4
512	10	522	2

How Hamming Codes Work

Hamming codes introduce additional bits, called parity bits, into the data. These parity bits are strategically placed within the data to allow the detection of errors. The positions of the parity bits are powers of two (e.g., positions 1, 2, 4, 8, etc.).

For example, in an 11-bit data block, we might have 4 parity bits, making it a 15-bit Hamming code.

- **Detecting Errors:** After transmission, the parity bits are recalculated and compared with the received parity bits. If there is any mismatch, the system can determine which bit is incorrect by checking the positions covered by the erroneous parity bits.
- **Correcting Errors:** If a single-bit error is detected, the Hamming code identifies which bit is incorrect (from the parity bits' positions) and corrects it by flipping the bit.

Example

In this simple example we encode 4 bits of data into 7 bits by adding 3 parity bits.

1. **Data Bits:** Let's say we want to transmit the 4-bit data **1011**.

From:

<https://edu.iit.uni-miskolc.hu/> - Institute of Information Science - University of Miskolc

Permanent link:

https://edu.iit.uni-miskolc.hu/tanszek:oktatas:techcomm:error_detection_and_correction?rev=1728238582

Last update: 2024/10/06 18:16

